

CLAIMS

The following listing of claims replaces all prior versions and listings of claims in the above-referenced application:

- 1 1. (Previously presented) A rate adaptive system for optical
2 communication networks comprising:
3 a plurality of optical transceivers capable of transmitting and receiving optical
4 signals at a plurality of rates to each other, and
5 an optical fibre linked to said optical transceivers, said system configured to
6 cause said optical transceivers to transmit and receive optical signals at an initial rate
7 and to adapt said initial rate based upon an error condition responsive to an optical
8 signal parameter by causing said optical transceivers to transmit and receive at a
9 different rate, wherein a rate of data being forwarded per unit time is adjusted by
10 inserting invalid data which can be identified and ignored by a downstream process.
- 1 2. (Previously presented) The system of claim 1, wherein said error
2 condition is a failure to synchronize a received signal.
- 1 3. (Previously presented) The system of claim 1, wherein said system
2 is further configured to calculate an error coefficient based on said received signals,
3 and said error condition comprise said error coefficient exceeding a predefined range.
- 1 4. (Previously presented) The system of claim 1, wherein said initial
2 rate is lowered according to predefined percentages of said initial rate in response to
3 said error condition.
- 1 5. (Previously presented) The system of claim 4, wherein said
2 percentages are selected from the group of 75, 50 and or 25 percent of said initial rate.

1 6. (Previously presented) The system of claim 1, wherein said initial
2 rate is 10 Gb/s.

1 7. (Previously presented) The system of claim 1, wherein said system
2 is configured to operate in an optical Ethernet network.

1 8. (Previously presented) The system of claim 1, wherein said system
2 is further configured to notify a network operator in the event of said error condition.

1 9. (Previously presented) A rate adaptive method for operating an
2 optical communication network, comprising:
3 transmitting data at an initial rate,
4 receiving said data at said initial rate,
5 evaluating said data responsive to a parameter observed on an optical signal to
6 determine if an error condition exists, and
7 adapting said rate based upon said evaluation by transmitting and receiving at
8 a different rate, wherein transmitting and receiving comprises inserting invalid data
9 which can be identified and ignored by a downstream process.

1 10. (Previously presented) The method of claim 9, wherein adapting
2 said rate comprises lowering said initial rate according to predefined percentages of
3 said initial rate in response to said error condition.

1 11. (Previously presented) The method of claim 10, further comprising
2 notifying a network operator in the event of said error condition.

1 12.-13. (Cancelled)